



Covet International
27 / 131 Hyde St
Yarraville VIC 3013
t: +613 9398 8128
e: info@covet.com.au
w: covet.com.au

Title:

Ever Art Wood® Aluminium Express Panels – Specification Guide

1 INSTRUCTIONS

The following is an example specification for Ever Art Wood Express Panels to be used for external cladding or interior lining. Please note that the areas highlighted below require input based on the requirements of the project.



Tip:

To copy the specification from PDF, select the text and right click to copy. When pasting in the word document, right click and paste as Keep Text Only to keep the formatting.

2 PRODUCTS

2.1 Metal Cladding/Lining

- A. Interlocking, aluminium sheeting cladding/lining system concealed fixed.
- B. Manufacturer/ reference: Covet International/ Express Panel Ever Art Wood - Interlocking Roll Formed Solid Aluminium Sheet.
 - 1. Type and material: Interlocking, roll formed aluminium sheeting.
 - 2. Thickness: 0.8mm.
 - 3. Finish:
 - a) Type: Timber look, exterior grade polymer wrap
 - b) Thickness: 0.2mm
 - c) Colour: Burakku Suchi-ru, Burakku Erumu, Chakooru Gurei, Kakicha, Kurocha, Daaku Pain, Burakku Eboni, Weebu Mahogani*, Buraun Eboni, Neikiddo Moku, Pain, Riigaru Oku, Kuri Masame, Biera Oku, Buraun Gurei, Kurashikku, Kareiro, Oku, Supuringu Oku*, Howaito Pain.***
 - 4. Overall thickness (sheeting and finish): 1mm.
 - 5. Joints:
 - a) Type: Expressed/ Recessed. ***
 - b) Size: 5mm to 18mm.***
- C. Additional Information:
 - 1. Support framing: Top hats, providing a completely flat surface appearance. / Corrosion resistant metal support framing mechanically fixed to substrate/ primary structure, to suit the service conditions.***
 - 2. Intermediate layer(s): Waterproofing/ vapour control layer where required (installed before support framing).
 - 3. Insulation: Refer to Type INS-***/ Thermal insulation as required.***
 - 4. Fire, smoke and acoustic stopping: Concealed and as required, to comply with the NCC.
- D. Fixing: Concealed fixed.
- E. Performance requirements:
 - 1. NCC fire hazard classification:
 - a) Spread of flame index: 0.
 - b) Group: 1.
 - 2. Acoustic rating: Rw *** dB/ Refer to the Acoustic Report/ Not applicable.***
- F. Datasheet: <https://www.covet.com.au/express-panel-cladding>
- G. Lead Time: 10-12 weeks.